


Hilfsmittel®

Pediatric Bacterial / Viral Filter



Product Feature

- Machine End Device
- Clear Casing
- Electrostatic Media
- 22M / 15F-15M ISO connectors
- Transparent housing
- WITH gas sampling port only
- Individual packed, available in sterile or non-sterile

Cat. No.	Description	Pack Per Box																											
CM-AO-9060	Pediatric Bacterial / Viral filter WITH gas sampling port	50																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40%;">Clinical Indication</td> <td>Short Term Anesthesia</td> </tr> <tr> <td>Tidal Volume Range</td> <td>≥90 mL</td> </tr> <tr> <td rowspan="2">Penetration</td> <td>At 15 L.min⁻¹ (mean [range])</td> </tr> <tr> <td>Unused 0.55[0.47to0.69]% After 3h simulated use 0.51[0.45to0.56]%</td> </tr> <tr> <td rowspan="2">Pressure Drop</td> <td>At 15 L.min⁻¹</td> </tr> <tr> <td>Used 65Pa Increase after 3h simulated use 3Pa</td> </tr> <tr> <td>Moisture Output</td> <td>At 0.25 L tidal vol. 15g.m⁻³</td> </tr> <tr> <td>Weight</td> <td>18g</td> </tr> <tr> <td>Dimensions (Diameter x L)</td> <td>52 x 66 mm</td> </tr> <tr> <td>Dead Space</td> <td>34 mL</td> </tr> <tr> <td rowspan="2">Connector</td> <td>Compliance with BS EN 1281-1</td> </tr> <tr> <td>Patient End 15F / 22M Machine End 15M</td> </tr> <tr> <td>Resistance to flow</td> <td>70 Pa @ 15 L.min⁻¹</td> </tr> <tr> <td>Filtration Efficiency</td> <td>99.999% Efficiency</td> </tr> <tr> <td>Casing Material</td> <td>Styrolux</td> </tr> </table>			Clinical Indication	Short Term Anesthesia	Tidal Volume Range	≥90 mL	Penetration	At 15 L.min ⁻¹ (mean [range])	Unused 0.55[0.47to0.69]% After 3h simulated use 0.51[0.45to0.56]%	Pressure Drop	At 15 L.min ⁻¹	Used 65Pa Increase after 3h simulated use 3Pa	Moisture Output	At 0.25 L tidal vol. 15g.m ⁻³	Weight	18g	Dimensions (Diameter x L)	52 x 66 mm	Dead Space	34 mL	Connector	Compliance with BS EN 1281-1	Patient End 15F / 22M Machine End 15M	Resistance to flow	70 Pa @ 15 L.min ⁻¹	Filtration Efficiency	99.999% Efficiency	Casing Material	Styrolux
Clinical Indication	Short Term Anesthesia																												
Tidal Volume Range	≥90 mL																												
Penetration	At 15 L.min ⁻¹ (mean [range])																												
	Unused 0.55[0.47to0.69]% After 3h simulated use 0.51[0.45to0.56]%																												
Pressure Drop	At 15 L.min ⁻¹																												
	Used 65Pa Increase after 3h simulated use 3Pa																												
Moisture Output	At 0.25 L tidal vol. 15g.m ⁻³																												
Weight	18g																												
Dimensions (Diameter x L)	52 x 66 mm																												
Dead Space	34 mL																												
Connector	Compliance with BS EN 1281-1																												
	Patient End 15F / 22M Machine End 15M																												
Resistance to flow	70 Pa @ 15 L.min ⁻¹																												
Filtration Efficiency	99.999% Efficiency																												
Casing Material	Styrolux																												

CoMcorde Medical (M) Sdn. Bhd.

No. 1, Jalan 11/32B,
TSI Business Industrial Park,
6½ Mile Off Jalan Kepong,
52000 Kuala Lumpur
Malaysia



Tel No 603-62433245

Fax No 603-62433246

Website

www.comcorde.com.my

Email

sales@comcorde.com.my

